

MATERIAL SAFETY DATA SHEET

Product: E-Z Seal® Flashing

Effective: August 16, 2006
Supersedes: January 4, 2006

Page 1 of 3

SECTION I

Company Name
Fortifiber Corporation

Emergency Telephone No.
508-222-3500

Address: 55 Starkey Ave., Attleboro, MA 02703

Chemical Name & Synonyms
N/A

Trade Name & Synonyms
EZ- Seal® Flashing

Chemical Family
Flashing: Polyolefin & Adhesive
Release Liner: Paper or Polyolefin

Formula
N/A

SECTION II - INFORMATION ON INGREDIENTS

Unlisted ingredients are not considered hazardous as defined by 21CFR 1900.1210 (OSHA Hazards Communications Law) paragraph (b) (5) (iv)

<u>Chemical</u>	<u>Percent</u>	<u>OSHA PEL</u>	<u>ACGIH TLV</u>
Hydrocarbon Oil	< 1%	5 mg / M ³ *	5 mg / M ³ *
LD50: No Data Found	LC50: No Data Found		

* These exposure limits are for mineral oil mist, a material related to hydrocarbon oil mist
ACGIH STEL: 10 mg / M³

SECTION III - PHYSICAL DATA

Boiling Point (°F.)
N/A

Specific Gravity (Water=1)
< 1.0

Vapor Pressure (mmHg.)
N/A

Percent, Volatile by Volume (%)
N/A

Vapor Density (Air=1)
N/A

Evaporation Rate(Butyl Acetate=1)
N/A

Solubility in Water Negligible

Appearance & Odor: Polyolefin film reinforced with scrim with adhesive strip applied along one edge and laminated to a release liner.

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

Flash Point / Method: 484°F COC, 288°C

Flammable Limits N/A LeL N/A/VeL N/A

Extinguishing Media: Water fog, CO₂, Dry Chemical, chemical foam. Using a direct, straight water stream may tend to spread a fire.

MATERIAL SAFETY DATA SHEET

Product: E-Z Seal® Flashing

Effective: August 16, 2006
Supercedes: January 4, 2006

Page 2 of 3

SECTION IV - FIRE AND EXPLOSION HAZARD DATA(cont'd)

Special Fire Fighting Procedures: Wear self-contained breathing apparatus and protective clothing to prevent contact with skin and eyes. Avoid using direct, straight water stream on molten material to reduce splattering and spreading of the fire.

Unusual Fire and Explosion Hazards: None known. Refer to NFPA Pamphlet No.654, "Prevention of Fire and Dust Explosions in the Chemical, Dye, Pharmaceutical and Plastics Industries".

SECTION V - HEALTH HAZARD DATA

Threshold Limit Value Not established

Effects of Overexposure

INHALATION: Above 180°C, irritating vapors may be released.

EYES: Low hazard for normal industrial handling.

SKIN: Molten material will produce thermal burns.

INGESTION: Not an anticipated route of exposure. Small amounts are not anticipated to be harmful.

Emergency and First Aid Procedures

INHALATION (from overheating as above): Vapors may cause irritation of the nose, throat and respiratory tract. Continued exposure may cause headaches and dizziness.

SKIN: If burned by contact with molten material, cool as quickly as possible and see a physician for treatment of burn.

Note to Physicians: Burns should be treated as thermal burns. Do not attempt to remove solidified plastic from the skin as severe tissue damage could result. Plastic will come off as healing occurs, therefore removal from the skin is not necessary. Mineral oil may be used to loosen the material if removal is desired.

INGESTION: If person can swallow, give one glass of water or milk. Do not induce vomiting. Get immediate medical attention. Never give anything by mouth to an unconscious person.

SECTION VI - REACTIVITY DATA

Stability: Stable X Unstable _____

Conditions to Avoid: Fire or exposure to strong oxidizing agents such as nitric and sulfuric and halogen and chlorinating agents.

Hazardous Polymerization: May Occur _____ Will not Occur X .

Hazardous Decomposition Products: As with any organic material, combustion will produce carbon monoxide, acrolein, and aldehydes.

MATERIAL SAFETY DATA SHEET

Product: E-Z Seal® Flashing

Effective: August 16, 2006
Supercedes: January 4, 2006

Page 3 of 3

SECTION VII - SPILL OR LEAK PROCEDURES

Steps to be Taken in Case Material is Released or Spilled: N/A

Waste Disposal Method

Incineration or landfill. Observe all federal, state and local laws concerning health and the environment.

SECTION VIII - SPECIAL PROTECTION INFORMATION

Respiratory Protection N/A

Ventilation: - Local Exhaust N/A
Special N/A

Mechanical N/A
Other N/A

Protective Gloves

Yes - To avoid cuts

Eye Protection

Safety glasses, ANSI Std. 287.1

Other Protective Equipment

None

Work/Hygienic Practices

Avoid unnecessary exposure to dust and fibers.

SECTION IX - SPECIAL PRECAUTIONS

Precautions to be Taken in Handling and Storing

Do not store near open flame.

Use reasonable care and caution in handling.

Other Precautions N/A

DISCLAIMER: The information provided herein is believed to be accurate but is not warranted to be whether it originated with Fortifiber Corporation or not. Much of the information contained in this Material Safety Data Sheet originates from suppliers: this information cannot be warranted by Fortifiber Corporation to be correct or appropriate for the recipient's intended use. Recipients are advised to confirm in advance of need that the information is current, applicable and suitable to their circumstances.
